

BATTERY RELATED PRODUCTS



M-750 Basic Switch

Labeled UL 707B. Rating: 500A intermittent, 310A continuous, 6-36V DC. Electrical ratings on UL labels are conservative. Use with either alternators or generators. Make before break design permits operation through the three On position with the engines running. Engines should always be shut down before turning to Off. Wiring instructions are included.



Straight Type



Right Angle Type



Left Elbow Type



Right Elbow Type

Wire Ga	Fits Type	Straight Stock No.	Right Angle Stock No.	Left Elbow Stock No.	Right Elbow Stock No.
6	Universal	36300	---	---	---
4	Universal	36301	---	---	---
2	Positive	36302	---	---	---
2	Negative	36303	---	---	---
1	Positive	36304	---	---	---
1	Negative	36305	---	---	---
1/0	Positive	36306	36320	36332	36342
1/0	Negative	36307	36321	36333	36343
2/0	Positive	36308	36322	36334	36344
2/0	Negative	36309	36323	36335	36345
3/0	Positive	36310	36324	36336	36346
3/0	Negative	36311	36325	36337	36347
4/0	Positive	36312	36326	---	---
4/0	Negative	36313	36327	---	---

Battery Jumper Terminals

Includes color coded rubber cap, solid brass studs, brass hex nuts brass lock washers



36660 Post with red cap for positive terminals

36661 Post with black cap for negative terminals